999.00 EUR
incl. 19% VAT, plus shipping

- VGA/HDMI Dual !
- 9-24VDC !
- 2x MiniPCIe !
- 2x COM !

Support: Specifications | Manual [EN]

Limited offer. As long as stock lasts !

Excellent as a router. 2x Intel WG82574L Gigabit LAN connections, high NAT performance thanks to Intel 1.86Ghz Dual-Core Atom CPU, 3G / 4G / LTE / 5G modem or WLAN upgradeable via 2x mini-PCIe slot. 2x COM port. Fanless, small, energy efficient, strong!

Scope of supply : DFI EC800-CD2041 (2GB RAM/16GB SSD), 12V 60W AC/DC power adapter with power cord, 2x metal mounting adapter

CPU	Intel® AtomTM D2550, 1.86GHz, 2x 512K L2, 10W TDP, dual-core
Chipset	Intel® NM10 Express Chipset
RAM	2GB DDR3 onboard
Graphics	Intel® GMA 3650 • 1 VGA port supports display resolution up to 1920x1200 • 1 micro HDMI port supports display resolution up to 1920x1080 • Smooth Video Playback - Supports hardware decoders (H.264, VC-1, MPEG-4) with Full HD 1080p video playback capability
Storage	• 1 CFast socket • 1 mSATA module via a Mini PCIe slot (16GB Module included)
Ethernet	2x Intel® WG82574L Gigabit Ethernet controllers (DUAL LAN)
Audio	• Realtek® ALC886 7.1-channel High Defintion Audio • 1 line-out and 1 mic-in
COM	• 2 DB-9 ports (RS232/422/485) • Supports RS485 auto direction control

Expansion	• 3 Mini PCIe slots - 2 slots for communication : One slot supports PCIe x1, USB, and LPC signals for Wi-Fi module or LPC module : One slot supports PCIe x1, USB, and 3G signals for 3G or GPRS module - 1 slot for storage : Supports mSATA module
Front I/O	• 1 SIM card socket • 1 CFast • 1 DB-9 RS232/422/485 COM • 1 mic-in• 2 LAN• 4 USB 2.0 (Type A) • 1 CFast socket • 1 status LED • 1 hdd LED • 1 reset button • 1 power button with LED
Power	9~24V DC power input voltage
Environment	• Temperature - Operating: 0oC ~ 60oC - Storage: -40oC ~ 80oC • Humidity - Operating: 10% to 85% non-condensing - Storage: 10% to 90% non-condensing
Construction	Aluminium
Mounting	Wall/VESA/DIN Rail mount
Dimensions	161mm x 32mm x 108.2mm (W x H x D)
Weight	700g
OS Support	• Windows XP, WES 2009, POSReady 2009 • Windows 7 (32-bit), WES 7 (32-bit) • Linux
Other features	Watchdog Timer function
Certification	• CE • FCC Class A • RoHS • UL • CCC • KC